



## STARCO AS Dumper



Dimension	Pattern	SI 1	LI 1	57 07562 +	TT/TL	mm	mm	kg	km/h	bar	Wheel	E-mark
12"												
7.00-12	STARCO AS Dumper II	A8	95	371061	Tyre TL	691	198	690	40	3,1	5.00	Yes
15"												
400/50-15	STARCO AS Dumper II	A8	121	363790	Tyre TL	780	380	1450	40	3	13	Yes
15,3"												
255/75-15.3	STARCO AS Dumper	A8	119	137865	Tyre TL	775	256	1360	40	3,1	9.00	Yes
295/80-15.3	STARCO AS Dumper	A8	131	137902	Tyre TL	855	287	1950	40	3,4	9.00	Yes
17"												
380/55-17	STARCO AS Dumper	A8	138	259642	Tyre TL	864	370	2360	40	2,8	13.00	Yes
380/55-17	STARCO AS Dumper II	A8	138	320274	Tyre TL	872	377	2360	40	2,8	13.00	Yes
18"												
315/80-18	STARCO AS Dumper	A8	148	146683	Tyre TL	981	314	3150	40	4,9	W9	Yes
425/50-18	STARCO AS Dumper II	A8	150	334189	Tyre TL	882	405	3350	40	3,5	14.00	Yes
20"												
405/70-20	STARCO AS Dumper II	A8	154	273044	Tyre TL	1090	407	3750	40	3,5	13.00	Yes
405/70-20	STARCO AS Dumper	A8	154	146690	Tyre TL	1084	409	3750	40	3,5	14.00	Yes



STARCO Dumper tires are of bias belted design - the preferred choice of the dumper industry due to its excellent lateral stability and superior capacity to withstand sidewall impact.

- ▶ Excellent traction and self cleaning
- ▶ For dumpers, loaders, digger-loaders and more
- ▶ Long lifetime
- ▶ Cost effective