



## Tianli F304



| Dimension  | PR | Pattern     | TT/TL   | 57 07562 + | mm  | mm  | kg   | km/h | LI 1 | SI 1 | bar | x     | E-mark |
|------------|----|-------------|---------|------------|-----|-----|------|------|------|------|-----|-------|--------|
| 17"        |    |             |         |            |     |     |      |      |      |      |     |       |        |
| 19.0/45-17 | 14 | Tianli F304 | Tyre TL | 109817     | 869 | 516 | 2800 | 40   | 144  | A8   | 3,9 | 16.00 | Yes    |
| 500/50-17  |    | Tianli F304 | Tyre TL | 104225     | 945 | 500 | 3550 | 40   | 152  | A8   | 3,8 | 16.00 | Yes    |
| 520/50-17  |    | Tianli F304 | Tyre TL | 110202     | 945 | 513 | 4375 | 40   | 159  | A8   | 3,6 | 16.00 | Yes    |



- ▶ Tubeless flotation tyre offers good self-cleaning characteristics
- ▶ Suitable for all agricultural implements especially for towed vehicles
- ▶ Offers high load capacity at low inflation pressures thus preventing damages to fields and crops
- ▶ Tyre for on and off-the-road agricultural service on trailers, tractors and large implements
- ▶ It offers enhanced durability due to the strong casing construction and compounds used