



Tianli FI



Dimension	PR	Pattern	TT/TL	57 07562 + mm	mm	kg	km/h	LI 1	SI 1	bar	x	E-mark
15,5"												
400/60-15.5	18	Tianli FI	Tyre TL	105628	875	405	3450	40	151	A8	4,5	13.00 Yes
22,5"												
500/60-22.5	16	Tianli FI	Tyre TL	106052	1186	483	3875	65	155	D	4	16.00 Yes
560/45-22.5	16	Tianli FI	Tyre TL	103884	1086	519	4500	40	160	A8	3,2	AG16.00 Yes
600/50-22.5	16	Tianli FI	Tyre TL	105710	1164	587	5150	40	165	A8	2,6	AG20.00 Yes
700/40-22.5	16	Tianli FI	Tyre TL	103815	1133	691	5300	40	166	A8	2,6	AG24.00 Yes
26,5"												
600/55-26.5		Tianli FI	Tyre TL	105277	1336	585	6000	40	170	A8	2,6	AG20.00 Yes
700/50-26.5	16	Tianli FI	Tyre TL	105307	1346	687	6700	40	174	A8	2,4	AG24.00 Yes
800/45-26.5		Tianli FI	Tyre TL	105369	1386	800	7300	40	177	A8	2,2	28.00 Yes



- ▶ Tubeless flotation tyre offers good self-cleaning characteristics
- ▶ Suitable for all agricultural implements especially for towed vehicles
- ▶ Offers high load capacity at low inflation pressures thus preventing damages to fields and crops
- ▶ Tyre for on and off-the-road agricultural service on trailers, tractors and large implements
- ▶ It offers enhanced durability due to the strong casing construction and compounds used